

PRODUCT TECHNICAL DATA SHEET

EXTRA GEL



Description	EXTRA GEL powder is made from high-yield sodium bentonite, specifically enhanced with additives to ensure optimal preparation of the drilling fluids. Its properties allow for effective borehole stabilization, high debris-carrying capacity, and excellent filtrate control even under extreme conditions. Drilling fluids prepared with EXTRA GEL inhibit the hydration of clay formations and remain stable even when contaminated with brackish water. EXTRA GEL bentonite is PFAS-free.			
Specifications	Moisture content	EN ISO 17892- 1:2014	%	< 13
	Bulk density	ISO 697: 1981	g/cm ³	3 0.8 ÷ 0.9
Dosage	Normal conditions:	20 ÷ 25 kg/m ³		
	Sand and gravel:	25 ÷ 35 kg/m ³		
Packaging	25 kg bags, 40 bags per pallet. Store in a dry place until use.			

All information contained in this document is deemed accurate and provided for information purposes only. Pancera Tubi does not provide any guarantee of any kind and does not assume any responsibility for the results obtained through the application of such information. Since the conditions of use of this product are beyond Pancera Tubi's control, the product is sold provided that the buyer carries out its own test to determine its suitability for the needed application. The purchaser assumes all risks relating to the use and handling of this product.